



Hydraulic Hexagonal Hose Brass Plumbing Nipple Fitting , Water Screw Plumbing Fittings

Our Product Introduction

for more products please visit us on brassbronzecasting.com

Basic Information

- Place of Origin: CHINA
- Brand Name: TSTY
- Certification: ISO9001 ISO14000
- Model Number: accordingly
- Minimum Order Quantity: 1000 sets
- Price: negotiation
- Packaging Details: Suitable for shipment
- Delivery Time: 3 weeks
- Payment Terms: L/C, T/T
- Supply Ability: 300,000 tons



Product Specification

- Materials: BRASS BRONZE
- Technic: Forging
- Packing: As Requests
- Standard: BSP
- Services: OEM ODM
- Head Code: Round
- Shape: Equal
- Name: Hydraulic Hexagonal Hose Brass Plumbing Nipple Fitting In Water
- Highlight: plumbing pipe fittings, brass plumbing fittings



More Images



Product Description

hydraulic Hexagonal hose brass plumbing nipple fitting in water

1/2 Inch Push-fit Barbed Elbows. These are lead free, have all approvals, easily removable/reusable.

| | |
|---------------------|--|
| Brand Name | TSTY / OEM available |
| Package | 1 pc in one poly bag, 10-12 pcs in one white or brown box, 100-120pcs in brown carton, OEM available |
| Payment Terms | Negotiated |
| Port of Departure | 250kms to Ningbo Port; 500kms to Shanghai Port, inland Yiwu Port or Customized; |
| Place of production | The Capital of brass valves Yuhuan, Taizhou, Zhejiang, China |
| Production Time | OEM order 45 days of production including new moulds, Existing products only need 30 -35 days after order confirmation |
| Applications | Water System |
| Main Material | MS58; HPB57-3; HPB59-1; CW617N; CW611N; CZ132(DZR); CW602N(DZR); OEM all type OEM are available |
| Size | 1/2" DN15; 3/4" DN20; 1" DN25; 1.1/4" DN32; 1.1/2" DN40; 2" DN50 are in common use, and reduced port available |
| Threaded | G (GB/T7307-2001) ; BSP (BS21-1957); BSP.F (BS-2779); BSP.T (BS-1957) |

The Push-Fit connection system is really taking hold. It's the easiest way to join copper, CPVC or PEX pipe in any combination ?

with no soldering, clamps, unions or glue. Just insert the pipe and the stainless steel teeth bite down and grip tight, while a specially formulated O-ring compresses to create a perfect seal. Disassembly is just as fast using the simple disconnect tool. So fittings and valves can be easily changed and reused. They can even be rotated after assembly for easier installation in tight spaces. Get a grip on your next plumbing project.



Packing :



上海天申铜业集团
SHANGHAI TIANSHEN COPPER GROUP

Shanghai Tianshen Copper Group Co.Ltd



brassbronzecasting.com

RM 4 A-D, No. 728 Middle Xizang Road, Huangpu District, Shanghai, China